


AGRITEC SUTO 10W-30

Product Code: AGR013 | **Revision:** 20251023



High-quality mineral oil based super universal tractor oil.

Available Pack Sizes



Applications

A premium-quality super universal tractor oil formulated from a blend of carefully selected mineral base oils and specialised additive technology. Suitable for use in four-stroke petrol and diesel engines, hydraulic systems and transmissions, including equipment with oil-immersed wet brakes. It features a very low pour point and a high viscosity index, ensuring minimal wear during cold starts while maintaining an effective lubrication film at elevated temperatures. This makes it a truly universal oil capable of delivering reliable performance under severe operating conditions.

Recommended by Aztec Oils as suitable for the following applications

ACEA E3
API (Engine) SF/CG-4
API (Transmission) GL-4
Allison C4
Case MS 1204/1206
Case New Holland MAT 3525
Caterpillar TO-2
Ford M2C134-D, M2C159-B/C
John Deere J27, J20C
MAN 271
Massey Ferguson M1135, M1139, M1143, M1144, M1145
New Holland 410B
Mercedes-Benz 228.1
ZF TE-ML 06B, 06C, 07B, 07D

Benefits

- Good anti-foaming and air release properties.
- Helps reduce wet brake squawk & chatter.
- Powerful anti-corrosion inhibitors which protects all working components.
- Provides excellent anti-wear protection.
- Reduced engine deposits and oil thickening.
- Universal application reduces lubricant stock and prevents misapplication.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4062	0.868
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	70
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	10.8
Pour Point (°C)	ASTM D97	-35
Viscosity Index	ASTM D2207	144

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.