

FUEL HUB

Compact

Model (FHC-1100L/291G)

The FUEL HUB Compact FHC-1100L is designed for the safe and secure storage of various industrial lubricants and hazardous liquids worldwide.



Specifications

	Metric	US	Imperial
Capacity	1100 Litres	291 Gallons	242 Gallons
Length	1374 mm	54 1/16"	54 1/16"
Width	1086 mm	42 12/16"	42 12/16"
Height	1270 mm	50"	50"
Outer Tank Thickness	4 mm	2/16"	2/16"
Inner Tank Thickness	4 mm	2/16"	2/16"
Weight, Tare	634 kg	1397 lbs, 12oz	1397 lbs, 12oz
Weight, Laden	1519 kg	3348 lbs, 13oz	3348 lbs, 13oz
Safe Fuel Fill Level	1045 Litres	276 Gallons	230 Gallons

Approvals and Certifications

UK & Europe

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design

USA & Canada

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design

FUEL HUB

Compact

Model (FHC-2250L/594G)

The FUEL HUB Compact FHC-2250L is designed for the safe and secure storage of various industrial lubricants and hazardous liquids worldwide.



Specifications

	Metric	US	Imperial
Capacity	2180 Litres	576 Gallons	480 Gallons
Length	2294 mm	90 5/16"	90 5/16"
Width	1086 mm	42 12/16"	42 12/16"
Height	1270 mm	50"	50"
Outer Tank Thickness	4 mm	2/16"	2/16"
Inner Tank Thickness	4 mm	2/16"	2/16"
Weight, Tare	925 kg	2039 lbs, 4oz	2039 lbs, 4oz
Weight, Laden	2737 kg	6034 lbs, 1oz	6034 lbs, 1oz
Safe Fuel Fill Level	2050 Litres	542 Gallons	451 Gallons

Approvals and Certifications

UK & Europe

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design

USA & Canada

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design

FUEL HUB

Compact

Model (FHC-3000L/793G)

The FUEL HUB Compact FHC-3000L is designed for the safe and secure storage of various industrial lubricants and hazardous liquids worldwide.



Specifications

	Metric	US	Imperial
Capacity	3000 Litres	793 Gallons	660 Gallons
Length	2294 mm	90 5/16"	90 5/16"
Width	1546 mm	60 13/16"	60 13/16"
Height	1270 mm	50"	50"
Outer Tank Thickness	4 mm	2/16"	2/16"
Inner Tank Thickness	4 mm	2/16"	2/16"
Weight, Tare	1123 kg	2475 lbs, 10oz	2475 lbs, 10oz
Weight, Laden	3810 kg	8399 lbs, 10oz	8399 lbs, 10oz
Safe Fuel Fill Level	2850 Litres	753 Gallons	627 Gallons

Approvals and Certifications

UK & Europe

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design

USA & Canada

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design