

Water & Energy
Hot Water Energy Storage
UK & ROI

NEW
Extended Heat
Pump Range

Including HP Slimline &
HP Cylinder with
Integral Buffer

Product Overview

Albion Aerocyl

Unvented Hot Water Cylinders & Buffer Tanks for Heat Pump Systems



kingspancylinders.com



Product Info

Albion Aerocyl


All cylinders supplied with:



Key Features†:

- 28mm coil heat exchanger for maximum heat transfer rated up to 32kW**
- Suitable for use with a wide range of heat pumps available on the market
- Mains pressure hot water (regulated up to 3 bar) for powerful showers
- High flow rates - ideal for multiple bathrooms and fast filling of baths
- Well insulated with low heat loss
- Oxygen purge welded Duplex stainless steel inner vessel for superior corrosion resistance
- Guaranteed# for 10 years on Duplex inner vessel against manufacturing defects and 2 years on parts

Buffer Tank (Heating System)



Connections


- | | |
|--|---|
| A 22mm Cold feed with dip pipe to diffuser in bottom of cylinder | H Open vent - 22mm Compression (3/4" Male BSP without nuts) |
| B 22m Hot water outlet | I Flow - 22mm Compression (3/4" Male BSP without nuts) |
| C Immersion heater* | J Return - 22mm Compression (3/4" Male BSP without nuts) |
| D1 22mm Heat pump coil connections | K Inspection hatch 1 3/4" Female boss & blanking plate |
| D2 22mm Solar coil connections | |
| E Temperature & pressure relief valve* | |
| F 22mm Secondary return (for cylinders with a capacity of 210L and above only) | |
| G Dry stat pocket | |




* Factory fitted to a cylinder (not buffer tanks). **Subject to delivering the required heat load to the coil through required flow rates and pipe sizing.




Selected models supplied with:



Indirect Heat Pump Cylinders (DHW)



Indirect Heat Pump & Solar Cylinders (DHW)



Form Factor	Nominal Capacity (Litres)	Height (mm)	Diameter (mm)	Buffer Tank	Codes		ErP	
					Indirect Heat Pump Cylinder	Indirect Heat Pump & Solar Cylinder	Rating	Standing Loss (W)
Standard	60	714	475	HPB60ERP	-	-	C	47
	90	1090	475	HPB90ERP	-	-	C	58
	150	1117	550	HPB150ERP	HP150ERP	-	C	59
	180	1305	550	HPB180ERP	HP180ERP	HPS180ERP	C	67
	210	1493	550	HPB210ERP	HP210ERP	HPS210ERP	C	75
	250	1744	550	-	HP250ERP	HPS250ERP	C	84
	300	2057	550	-	HP300ERP	HPS300ERP	C	93
Slimline	150	1458	475	-	HP150SLMERP	-	C	66
	180	1708	475	-	HP180SLMERP	-	C	72
	210	2021	475	-	HP210SLMERP	-	C	87

Note: Do not use immersion heaters as the primary heat source.
 # All guarantees subject to Terms and Conditions including an annual servicing requirement.

†Note: Key Features refer to cylinder models only.
 All dimensions ±3mm unless stated otherwise.


New Albion Aerocyl Unvented HP Cylinder with Integral Buffer

Key Features:

- Space saving solution with half the footprint of a standard installation
- 28mm coil heat exchanger for maximum heat transfer rated up to 32kW**
- Mains pressure hot water (regulated up to 3 bar) for powerful showers
- Good flow rates for fast filling of baths, ideal for multiple bathrooms
- Well insulated with low heat loss
- Guaranteed# for 10 years on Duplex inner vessel against manufacturing defects and 2 years on parts

Connections

- | | | |
|---------------------------------------|--|--|
| A 22mm Inlet control set cold feed | F 22mm Secondary return | L 28mm Flow - HP |
| B 22mm Hot water draw-off | G 10mm Dry stat pocket | M 28mm Return - HP |
| C1 3kW Immersion heater | H Circulating pump* | N Filling loop |
| C2 3kW Immersion heater* | I 28mm Two port valve to heating system* | O Balancing bypass valve |
| D Tee to potable expansion vessel | J 28mm Three port diverter valve | P Anti splash tundish |
| E Temperature & pressure relief valve | K Flow regulator* | Q Air release valve |
| | | R Return from heating system (behind pump) |



Nominal Capacity (L)		Height (mm)	Dia. (mm)	Codes	ErP	
Cylinder	Buffer				Rating	Standing Loss, (W)
180	50	1711	550	HPIB180/50P0ERP	C	64
210	50	1899	550	HPIB210/50P0ERP	C	68
240	50	2103	550	HPIB240/50P0ERP	C	80




Buffer Kit - 1054006

- Circulator pump & cable
- 28mm two port valve
- 3kW Immersion heater & O-ring

Heat Pump Kit - 1054015

- Flow regulator with sight glass
- Magnetic filter with 28mm isolation valves

*Supplied separately as part of a kit. **Subject to delivering the required heat load to the coil through required flow rates and pipe sizing.

 KingspanWaterandEnergy
 @KingspanWatEner
 KingspanWaterEnergy

Kingspan Water & Energy Ltd.
 Tadman Street | Wakefield
 West Yorkshire | WF1 5QU
 UK: hotwater@kingspan.com

T: (GB) +44 (0) 345 260 0258
 T: (NI) +44 (0) 28 3836 4520
 T: (ROI) +353 (0) 42 969 0022
 ROI: cylindersinfo@kingspan.com

We take every care to ensure that the information in this document is accurate at the point of publication. Specification may vary (within a small parameter) due to manufacturing process variations or environmental conditions. All images are for illustration purposes only and should not be taken as binding. The actual product may vary, and specification/ dimensions/ colour/ other attributes may differ.

To ensure you are viewing the most recent and accurate product information, please visit this link:
<https://kingspancylinders.com>

@Kingspan, the Lion Device and Albion Aerocyl are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All rights reserved.

Registered in Country No.NI017631. Registered Office: 180 Gilford Road, Portadown, Co. Armagh, BT63 5LF. VAT GB412 5124 03

